

GRAVIMETRIC PACKING



PRK.01B-00.00.5010.00



PRK.01BM-00.00.1020.00



PRK.01B-00.00.0030.OP

FNS.01

INTENDED USE

Semiautomatic devices of PRK.01 series are designed to pack liquid, foaming, low viscosity chemical and technical products of enamel of PF type, paints of MA and NTs type, primers of PF and GF types, organic impregnations on the basis of white spirit, solvent as well as water acrylic materials..

TECHNICAL CHARACTERISTICS	PRK.01	PRK.01M	PRK.02(022)	PRK.02M
Value of dose*, kg	1,0-30 (brutto)	1,0-30 (brutto)	1,0-30(netto)	1,0-30(netto)
Fallibility of batching, %, at most	±0,5	±0,5	±0,5	±0,5
Pressure of compressed air, kg/cm ₂		5-6		
Consumption of compressed air, m ₃ /h		3-25		
Overall dimension, m. at most	1,6×0,9×1,8	1,8×1,2×2,5	2,0×1,1×1,9	2,0×1,1×2,2
Weight, kg. at most		240		
Maintenance staff		1 operator		

* –continuously adjustable

SERVICE CONDITIONS : Machine is completely adapted for EX explosive environment operation (Russian GOZGORTECHNADZOR Certificate)

